



## OXYGEN CLEANER High Power Mould Removal



Easy, safe removal of mould and environmental pollution on all exterior timber, decks and outdoor furniture.

Harnessing the power of concentrated oxygen, timber easily comes back like new. All it takes is a little elbow grease, a scrubbing brush and a hose off.

Sodium percarbonate combined with selected

natural surfactants creates a powerful oxygen cleaner which is safe for the environment.

Combine with warm water as per instructions and apply with a garden sprayer. Wait ten minutes, easily remove the black with a scrubbing brush or deck broom, then hose clean.

**1kg concentrate will treat approx 50sqm**

Exterior timber will usually blacken over time due to the effects of wind blown tree spores and general biological and man induced pollutants.

Utilizing the concentrated cleaning power of pure oxygen (released when mixed with warm water); **NHC Oxygen Cleaner** removes contamination of black mould and UV degraded wood fibre from decks, cladding, pergolas and outdoor furniture. It is harmless to exterior surfaces such as timber, concrete, glass, terracotta tiles and slate.

Safe around pools. Take good care around delicate plants.

**Application:**

1. Into a plastic bucket, mix 1 scoop of powder per 1L of warm water (40deg, just cool enough to put your hand in). Make sufficient quantity to use in a garden sprayer. Stir well for 2-3 minutes, the product will foam as the oxygen activates.
2. Apply the mixture (using your garden sprayer) in manageable areas (2m x 2m), keep wet and avoid evaporation.
3. Thoroughly wet the area with the mixture and leave for 10 minutes. If the surface starts to dry out keep wet by reapplying the product.
4. Scrub in the direction of the grain using a stiff deck broom or scrubbing brush, keep wet with a trickle of hose water (wear rubber gloves).
5. Hose off the scrubbed area to reveal your clean timber.
6. Treat your timber to a coat of **NHC Exterior Oil** when dry.

**Ingredients:** Sodium Percarbonate, Sodium Carbonate, Sodium Citrate, Sodium Bicarbonate, Zeolite, Capryl Glucoside, Cellulose Gum.

**Maintenance:** Horizontal surfaces like decks tend to attract mould and pollutants quicker than vertical cladding. Rough sawn timber captures mould spores easier than dressed timber. An annual treatment with **NHC Oxygen Cleaner** every Spring is recommended but you can apply whenever the need arrives. Be sure to protect against checking and cracking by applying **NHC Exterior Oil** every 2-3 years or as required.

**CAUTION:**

While Oxygen Cleaner is safe to use, it will be harmful if swallowed and may cause mild skin irritation.

**FIRST AID:**

IF ON SKIN - wash with water and soap, rinse thoroughly.  
IF IN EYES - flush with copious amounts of fresh water for 15 minutes.  
IF SWALLOWED - do not induce vomiting, rinse mouth with copious amounts of fresh water, seek medical advice.  
tel: 0800 764 766

**FIRE:**

Use foam, dry chemical.  
Use breathing apparatus.  
Rapid oxygen evolution may increase intensity of fire.

**KEEP OUT OF REACH OF CHILDREN**